

# Fujitsu-Siemens 19" LCD Monitor L19\_W

-1440 x 900,500:1,8ms,2xD-SUB,Tilt

Produktnr.: S26361-K1104-V170 (S26361-K1104-V170)



## Fujitsu Siemens Flatskjerm SCALEOVIEW L19-1W

### SCALEOVIEW L19-1W

**An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L19-1W widescreen display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design, the SCALEOVIEW L19-1W fits perfectly into your home environment.**

Visible screen diagonal 19 inch (48.1 cm)

Resolutions

Pixels 1440 x 900

Pixels\* 1280 x 768

\* expanded

Picture size 410.4 x 256.5 mm

Colors 16.2 million

Pixel Pitch 0.285 mm

Frequencies

Horizontal 30 - 80 kHz

Vertical 60 - 75 Hz

Brightness (typical) 300 cd/m<sup>2</sup>

Contrast (typical) 500:1

Viewing angle (typical)

Horizontal 150°

Vertical 130°

Response time (typical) 8 ms

Plug and Play VESA DDC2B

Setting options

Brightness (Back light control)

Contrast, Volume control

Picture position (horizontal and vertical), H-size, Phase,

Color temperature and individual color setting

Auto-adjust (direct access key)

Activate factory settings

Menu language

OSD Language

English, German, Spanish, French, Italian, Russian, Swedish, Portuguese, Danish, Polish, Finnish

Base

Tilt angle  $-5^{\circ}$  /  $+20^{\circ}$

Audio characteristics

Audio signal input 3.5mm stereo phone jack

Audio output 2.5 W (L) + 2.5 W (R)

Electrical values (internal power supply)

Rated voltage 100 - 240 V

Frequency 50 - 60 Hz

Power draw

Max. <60 W

Stand by < 2 W

Protection class 1

Temperatures/ dimensions/ weight

Ambient temperature (to IEC721):

Working (recommended)  $5^{\circ}\text{C}$  to  $35^{\circ}\text{C}$

Storage  $-20^{\circ}\text{C}$  to  $60^{\circ}\text{C}$

Dimensions (H x W x D):

(with stand) 360 x 433 x 221.6 mm

Weight (Monitor only) 5.5 kg

Reliability

MTBF (demonstrated) 70,000 h

Lifetime of LCD backlight 50,000 h

(brightness > 50 % of original brightness)

Compliance with standards

Product safety EN60950

Ergonomics GS mark

ISO13406-2

(Pixel fault class II)

Radiation immunity and CE certification according RFI suppression to EC Directive

89/336/EEC

(EN55022/B, EN55024

EN61000-3-2/-3);

TCO'99

Video input 2 x D-SUB

Accessories

Power cable (1.5 m)\* For wall socket

(Euro-Schuko-Type CEE7)

Data cable (1.5 m)\* D-SUB (15-pin)

Audio cable (1.8 m)\* 3.5mm stereo phone jack

\* detachable on display

Special features

Standardized mounting interface according VESA FPMPI

(100 mm)

Kensington Lock

Order code S26361-K1104-V170

EAN: 4045827665403